



RING'S END Weatherization Systems

Product	RE Code	Units Per Pallet/Cse	Coverage	Order Quantity	Installation Best Practices
Weathermate™ Plus					
3' x 100'	DWRAP3	54 rolls	300 sq. ft./roll		Horizontal overlaps are 2". Vertical overlaps are 6". 12" overlap around inside & outside corners. Use cap or corrosive-resistant fasteners penetrating a minimum of 1/2" into nail bed every 16 inches, may vary depending on wind loads.
9' x 100'	DWRAP9	55 rolls	900 sq. ft./roll		
Weathermate™ Flashing & Sealants					
4" x 75' 3M Flashing	3MTAPE4	12 rolls	75 linear ft./roll		Apply to a clean and dry substrate. Must apply pressure to ensure proper adhesion.
6" x 75' 3M Flashing	3MTAPE6	8 rolls	75 linear ft./roll		
9" x 75' 3M Flashing	3MTAPE9	4 rolls	75 linear ft./roll		
Moistop Sealant	BMOISTOP	30 tubes	30 linear ft./tube		Apply 3/8" bead no more than 1/2" away from rough opening to ensure sealant is behind window flanges. Also ideal for sealing around penetrations.
Benjamin Obdyke Hydrogap®					
Hydrogap 5' x 100'	HYDROGAP	52 rolls	500 sq. ft./roll		4" overlap on horizontal seams. 6" overlap on vertical seams. 12" overlap on inside & outside corners. Must use cap or corrosive-resistant fasteners for installation.
Hydrogap SA 57" x 80'	HYGPSA	30 rolls	380 sq. ft./roll		Apply on clean, dry substrate. Must apply pressure to activate adhesive properly with stiff bristled broom, laminate roller, or zip roller.
Benjamin Obdyke Flashing & Sealants					
4" x 75' 3M Flashing	3MTAPE4	12 rolls	75 linear ft./roll		Apply to a clean and dry substrate. Must apply pressure to ensure proper adhesion.
6" x 75' 3M Flashing	3MTAPE6	8 rolls	75 linear ft./roll		
9" x 75' 3M Flashing	3MTAPE9	4 rolls	75 linear ft./roll		
Moistop Sealant	BMOISTOP	30 tubes	30 linear ft./tube		Apply 3/8" bead no more than 1/2" away from rough opening to ensure sealant is behind window flanges. Ideal for sealing around penetration.
Henry Blueskin™ VP100					
48" x 100' Blueskin VP100	BLUESK	36 rolls	400 sq. ft./roll		Apply on clean, dry substrate. 2" overlap on horizontal seams, 3" overlap on vertical seams and 6" around inside & outside corners. Apply pressure to activate adhesive with stiff bristled brush, laminate roller, or Zip roller. Can be applied vertically or horizontally.
Henry Flashing & Sealant Products					
4" x 75' Blueskin Butyl Flash	BTAPE4	12 rolls	75 linear ft./roll		Apply to clean, dry substrate; apply pressure to activate adhesive; can be used for sill pan flashing, leg, and header flashing around windows.
6" x 75' Blueskin Butyl Flash	BTAPE6	8 rolls	75 linear ft./roll		
9" x 75' Blueskin Butyl Flash	BTAPE9	4 rolls	75 linear ft./roll		
Moistop Sealant	BMOISTOP	30 tubes	30 linear ft./tube		Apply 3/8" bead no more than 1/2" away from rough opening to ensure sealant is behind window flanges. Ideal for sealing around penetration.
Henry 212 All Purpose Sealant	BLUESE	12 tubes	15 linear ft./tube		The only sealant approved to be used to terminate head flashing on VP100. Apply along the top edge where flashing and VP100 meet, continuing 2" down each side of head flashing.
Blueskin Spray Prep	BLUEPR	12 cans			Spray on non-wood substrates to achieve desired adhesion. Wait 45 sec. to apply self-adhered products. Don't use on rubberized asphalt.





RING'S END Weatherization Systems

Product	RE Code	Units Per Pallet/Cse	Coverage	Order Quantity	Installation Best Practices
Huber Zip System™					
Zip R-3 1" x 4' x 8' (Green)	ZIPR36	32 sheets	32 sq. ft./sheet		Follow zip sheathing installation best practices except for fastening. Use min .131" shank nail that penetrates a min of 1.5" into framing or 7/16" crown staple that penetrates min 1" into framing.
Zip R-6 1.5" x 4' x 8' (Green)	ZIPR66	31 sheets	32 sq. ft./sheet		
7/16" x 4' x 8' (Green)	ZIPWALL	80 sheets	32 sq. ft./sheet		Must be applied with code-approved fasteners and fastened through circles or squares that represent either 16" or 24" on center framing. Apply tape over seams using dotted lines for proper coverage and overlap. Make sure to use either 6" or double 3.75" tape on corners and in valleys.
7/16" x 4' x 10' (Green)	ZIPWALL10	70 sheets	40 sq. ft./sheet		
1/2" x 4' x 8' (Red)	ZIPROOF	70 sheets	32 sq. ft./sheet		
5/8" x 4 x 8' (Red)	ZROOF5SE	55 sheets	32 sq. ft./sheet		
5/8 x 4 x 8 T&G (Red)	ZIPROOF5	55 sheets	32 sq. ft./sheet		
Huber Flashing & Sealants					
3.75" x 90' Seam and Window Tape	ZTAPE	12 rolls	30 linear ft./roll		Apply to clean and dry substrate. Use zip roller to ensure proper pressure is applied for maximum performance and proper adhesion. Use 6" tape for corners and roof valley applications.
6" x 75 Seam and Window Tape	ZTAPE6	4 rolls	90 linear ft./roll		
6" x 20' Stretch Tape	ZST620	1 per box	75 linear ft./roll		
6" x 75' Stretch Tape	ZST675	1 per box	20 linear ft./roll		
10" x 20' Stretch Tape	ZST1020	1 per box	75 linear ft./roll		
10" x 75" Stretch Tape	ZST1075	1 per box	20 linear ft./roll		
Moistop Sealant	BMOISTOP	30 tubes	75 linear ft./roll		Apply 3/8" bead no more than 1/2" away from rough opening to ensure sealant is behind window flanges. Ideal for sealing around penetration.
Zip Roller	ZROLL	1	30 linear ft./tube		Required to apply pressure to seams and window flashing.
Drainage Mats					
Mortairvent 3mm 39" x 46.2'	MORTAIR3	24 rolls	150 sq. ft./roll		Run horizontally right to left over already applied WRB. On first bottom layer tuck fabric flap under itself to create insect screen. Additional rows should butt to the next row and ensure fabric flap overlaps row below in a shingle fashion. Once at the top, invert last row and tuck fabric flap under to create insect screen on top. Fasten with a capped or corrosive-resistant fastener min 1/2" in length every 3 sq. ft., sufficient enough to hold drainage mat until cladding is applied.
Mortairvent 6mm 39" x 46.2'	MORTAIR	18 rolls	150 sq. ft./roll		
Home Slicker 39.37" x 46.5'	SLICK	16 rolls	150 sq. ft./roll		Roll out over already installed WRB. Do not stretch slicker classic. Fasten with min 1/2" fasteners. Butt rows together. Cover entire surface where cladding will cover. At the top and bottom apply slick screen or window screen to create insect screen.